

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Germany



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name :

Sikafloor®-161 Part A

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Deutschland GmbH

Street/postbox : Kornwestheimer Str. 103-107

Town/City and Post Code : 70439 Stuttgart

Country : Germany

Telephone no. : +4971180090

Fax no. : +497118009321

e-mail address of person responsible for this SDS : EHS@de.sika.com

Emergency telephone number : +49-(0)173-6774799 (Only out of office hour)

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38
R43
N; R51/53

Human health hazards : Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Filled and modified epoxy resin

Characteristics

Ingredient name	CAS number	%	EC number	Classification
Reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	35-50	500-033-5	Xi; R36/38 R43 N; R51/53 [1]
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	2.5-5	271-846-8	Xi; R36/38 R43 N; R51/53 [1]
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	2.5-5	500-006-8	Xi; R36/38 R43 N; R51/53 [1]
benzyl alcohol	100-51-6	<25	202-859-9	Xn; R20/22 [1]
ethanol	64-17-5	1-5	200-578-6	F; R11 [2]
solvent naphtha (petroleum), light arom.	64742-95-6	<0.25	265-199-0	R10 Xn; R65 Xi; R37 R66, R67 N; R51/53 [1]

Date of issue : 11.08.2009.

MSDS no. : 121796

1/7

3. COMPOSITION/INFORMATION ON INGREDIENTS

1,2,4-trimethylbenzene	95-63-6	0.1-0.25	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53	[1] [2]
See section 16 for the full text of the R-phrases declared above					

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

- Inhalation** : Get medical attention if adverse health effects persist or are severe.
- Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Maintain an open airway. Seek immediate medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Obtain medical attention if symptoms occur.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6. ACCIDENTAL RELEASE MEASURES

- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.
- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- Packaging materials**
- Recommended** : Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
<input checked="" type="checkbox"/> ethanol	TRGS900 AGW (Germany, 7/2008). PEAK: 1920 mg/m ³ 15 minute(s). PEAK: 1000 ppm 15 minute(s). TWA: 960 mg/m ³ 8 hour(s). TWA: 500 ppm 8 hour(s).
1,2,4-trimethylbenzene	TRGS900 AGW (Germany, 7/2008). PEAK: 200 mg/m ³ 15 minute(s). PEAK: 40 ppm 15 minute(s). TWA: 100 mg/m ³ 8 hour(s). TWA: 20 ppm 8 hour(s).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.
- Exposure controls**
- Occupational exposure controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapour filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Reference number EN 374. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves. (0,4 mm), breakthrough time <30 min. Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

- Form** : Viscous mass.
- Colour** : Grey.
- Odour** : Faint odour.

Important health, safety and environmental information

- pH** : 6
- Flash point** : Closed cup: ~89 °C (192.2 °F)
- Density** : ~1.6 g/cm³ [20 °C (68 °F)]
- Solubility** : Insoluble in the following materials: water

10. STABILITY AND REACTIVITY

Stability	: The product is stable.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid release to the environment. Refer to special instructions/safety data sheet.
Materials to avoid	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION


Potential acute health effects

Inhalation	: May cause irritation.
Ingestion	: Irritating to mouth, throat and stomach.
Skin contact	: Irritating to skin. May cause sensitisation by skin contact.
Eye contact	: Irritating to eyes.
Chronic effects	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

12. ECOLOGICAL INFORMATION

Environmental effects	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
------------------------------	---

13. DISPOSAL CONSIDERATIONS

Methods of disposal	: Completely emptied packagings can be given for recycling. Packaging containing remains of dangerous substances, as well as packagings disposed of remains can be unharmed eliminated in accordance with the regulations.
Packaging	: ompletely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.  01 10* packaging containing residues of or contaminated by dangerous substances

For further details see www.sika.de

14. TRANSPORT INFORMATION


International transport regulations

ADR

	: UN3082
ADR Class	: 9
Classification code	: M6
Packing group	: III
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
Contains	: Epoxide resin
Label No.	: 9

IMDG

14. TRANSPORT INFORMATION

UN number : UN3082
IMDG Class : 9
Packing group : III
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
Contains : Epoxide resin
Emergency schedules (EmS) : F-A, S-F
Marine pollutant : 
Label no. : 9


IATA

UN number : UN3082
IATA Class : 9
Packing group : III
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
Contains : Epoxide resin
Label no. : 9


15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi, N
 Irritant, Dangerous for the environment
Contains :  reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)
 oxirane, mono[(C12-14-alkyloxy)methyl]derivs
 reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)
Risk phrases : R36/38- Irritating to eyes and skin.
 R43- May cause sensitisation by skin contact.
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases : S24- Avoid contact with skin.
 S37- Wear suitable gloves.
Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.
VOC content (EU) : VOC (w/w): 3.56%

National regulations

CLP CODE :  RE 1
Hazard class for water : 2 Appendix No. 4 (Gemäß VwVws vom 17. Mai 1999)
Remark : For activities with dermal exposure or inhalativ exposition with possible health hazards, occupational health checks have to be conducted (German regulation).

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and 3 : R11- Highly flammable.
R10- Flammable.
R20- Harmful by inhalation.
R20/22- Harmful by inhalation and if swallowed.
R65- Harmful: may cause lung damage if swallowed.
R37- Irritating to respiratory system.
R36/38- Irritating to eyes and skin.
R36/37/38- Irritating to eyes, respiratory system and skin.
R43- May cause sensitisation by skin contact.
R66- Repeated exposure may cause skin dryness or cracking.
R67- Vapours may cause drowsiness and dizziness.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications referred to in sections 2 and 3 : F - Highly flammable
Xn - Harmful
Xi - Irritant
N - Dangerous for the environment

History

Date of printing : 12.08.2009
Date of issue : **11.08.2009.**
Date of previous issue : **13.10.2008.**

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.