

# Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

Date of printing: 17.04.2008

Page: 1/5

Revised: 17.04.2008

SDS No.: 001-00010000.0000

## 1. Identification of the substance/preparation and company

Product

Product name

**Sika Seram 120HB**

Manufacturer/supplier information

Manufacturer/supplier:

GILAR LTD

Street/postbox:

Hamatechet St. Industrial Area

Town/City and Post Code:

Kadima

Country:

Israel

Phone:

+97298994000

Telefax:

+97298994003

General information:

Environment and Safety

Emergency information phone:

+972 (0) 98 99 40 07

## 2. Composition/information on ingredients

Chemical characterization

Mixture of cements, aggregates and additives (Cr+VI < 2 ppm)

Hazardous ingredients

Designation according to 67/548/EEC

CAS No.

Concentration

Danger symbols R phrases

· cement

65997-15-1

25 - 50 % Xi

41,37/38

266-043-4

## 3. Hazards identification

Hazards identification

Xi

Irritant

Information on hazards to man and to the environment

37/38

Irritating to respiratory system and skin.

41

Risk of serious damage to eyes.

## 4. First-aid measures

General instructions

In any case show the physician the Safety Data Sheet

After inhalation

In case of irritation when dust is inhaled, provide for plenty of fresh air.

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Summon a doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Product name: **Sika Seram 120HB**

Date of printing: 17.04.2008

Page: 2/5

Revised: 17.04.2008

SDS No.: 001-00010000.0000

## **5. Fire-fighting measures**

Suitable extinguishing media

foam

dry powder

water

Unsuitable extinguishing media for safety reasons

Not applicable.

Exposure hazard arising from the product, its combustion products or resulting gases

Carbon monoxide (CO)

Carbondioxide (CO<sub>2</sub>)

Nitrogen oxides (NO<sub>x</sub>)

Special protective equipment for fire-fighting

Use breathing apparatus.

Additional information

Product of itself does not burn.

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

## **6. Accidental release measures**

Personal precautions

Avoid dust formation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapour/dust/aerosol.

Environmental precautions

In case of entry into waterways, soil or drains,  
inform the responsible authorities.

Procedures for cleaning up

Pick up mechanically

When picked up, treat material as prescribed under heading "Disposal".

## **7. Handling and storage**

Handling

Instructions for safe handling

See chapter 8 / Personal protective equipment.

Avoid dust formation.

Use only in well ventilated areas.

Instructions for fire and explosion protection

Not applicable.

Storage

Requirements for storage rooms and containers

Keep sacks tightly closed and dry, in a weather-proof place

Combined storage instructions

Keep away from food, beverages and animal feedstocks.

Additional information regarding storage

Protect from atmospheric moisture and water

Product name: **Sika Seram 120HB**

Date of printing: 17.04.2008

Page: 3/5

Revised: 17.04.2008

SDS No.: 001-00010000.0000

**\* 8. Exposure controls/personal protection**

Personal protective equipment

General protective and hygiene measures

Do not inhale dust

Take care for sufficient ventilation or exhaust on the workshop place.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

Use barrier skin cream.

Respiratory protection

Dust protection mask

Hand protection

Nitrile Rubber gloves

Eye protection

Safety glasses /face shield

Body protection

Working clothes

**9. Physical and chemical properties**

Appearance

Physical state:

Powder

Colour:

grey

Data relevant to safety

Method

Flash point

not applicable

Auto-ignition temperature

not applicable

Vapour pressure at 20°C

not applicable

Loose bulk density

1.3 g/cm<sup>3</sup>

DIN 53468

Solubility in water

2%

at 20°C

pH value at 20°C

12.1

(c undefined)

Product name: **Sika Seram 120HB**

Date of printing: 17.04.2008

Page: 4/5

Revised: 17.04.2008

SDS No.: 001-00010000.0000

## **10. Stability and reactivity**

Materials to avoid/dangerous reactions

Hazardous reactions possible with:

Acids

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

## **\* 11. Toxicological information**

Sensitization

When skin contact:

Sensitization/allergic reaction possible.

Experience on humans

When skin contact:

May cause irritation.

When eyes contact:

irritation.

May cause irreversible damage to eyes.

When inhalation:

Irritation.

When swallowed:

Small amount may cause considerable health disorders.

## **12. Ecological information**

Additional information

Product is slightly water polluting.

Due to the high pH, aquatic organisms may be harmed.

Do not allow to enter waste water drain, waterways or soil.

Once cured, the product will unlikely have any adverse effect on the Environment.

## **13. Disposal considerations**

Product

Recommendations

Dispose of in accordance with local authority regulations.

See chapter 15, national regulations.

Packaging

Recommendations

Completely emptied packagings can be given for recycling.

Packaging that cannot be cleaned should be disposed of as product waste.

## **14. Transport information**

ADR/RID

Further Information

NO DANGEROUS GOODS

IMO/IMDG

Further Information

NO DANGEROUS GOODS

IATA/ICAO

Further Information

NO DANGEROUS GOODS

