

Sika® Fugafleks

Construction

Description □	One-component joint filler for all kinds of hard floor tiles.
Uses □	For the joints of tiles, marble, granite, etc.
Advantages □ □ □ □ □ □ □	- Good adhesion to surfaces, - Elastic, - In different colours, - Easy application, - Dirt proof if properly applied, - Resistant to abrasion and frost, - Non-toxic.
Application □ □ □ □	For a flowable mix use 40/100 water/dry material ratio. Mix until a homogeneous □ mix is obtained and fill the joints with a plastic spatula. For coloured material, colour pigment packs are added to the half of the mix water. □ Rest of the water is added to the wet mix after the coloured one.
Yield □	0,4-1 kg/m ²
Colour □	In various colours
Shelf Life □	6 months in original packs prevented from humidity
Packaging □	In 5 and 20 kg packs

Technical data sheet and label instructions have the priority.

The explanations given in the data sheet are correct and reliable as far as we know and they are in connection with our documentation. In case of applications beyond our control, our warranty is only valid in respect of the quality of the sold product. Our company reserves the right to make changes to the product formulations under the light of our new R&D studies. This technical data sheet is valid until a new one is printed and supersedes all of the former editions.

Sika Yapı Kimyasalları A.Ş.

Çamçeşme Mah. Sanayi Cad. Kaynarca 34899 Pendik / İstanbul
Phone: +90 216 494 19 90 Fax: +90 216 494 19 84 web: www.sika.com.tr

Regional Directorates: Adana | Ankara | Antalya | Bursa | İzmir | Trabzon

Phone | :0322 458 84 27 | 0312 482 06 06 | 0242 247 60 07 | 0224 225 63 80 | 0232 469 91 14 | 0462 326 14 73
Fax | :0322 458 04 05 | 0312 482 65 59 | 0242 241 95 92 | 0224 225 63 52 | 0232 459 34 66 | 0462 326 14 03

