

# Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

Date of printing: 02.11.2005

Page: 1/5

Revised: 18.04.2005

SDS No.: 014-00215065.0000

## 1. Identification of the substance/preparation and company

Product

Product name

**Sikafloor Proseal W**

Manufacturer/supplier information

Manufacturer/supplier:

Sika S.A.

Street/postbox:

Carretera de Fuencarral, 72 Pol Ind

Town/City and Post Code:

28108 Alcobendas (Madrid)

Country:

España

Phone:

91 662 18 18

Telefax:

91 662 19 38

General information:

Emergency information phone:

91 662 18 18

Durante el horario normal de trabajo

## \* 2. Composition/information on ingredients

Chemical characterization

Aqueous dispersion of butadiene-styrene

Hazardous ingredients

Designation according to 67/548/EEC

CAS No.                      Concentration      Danger symbols R phrases

EC No.

· Troysol LAC

0.1 - 1 %      Xn,N

48/20,38,41,51/53

· (2-methoxymethylethoxy)propanol

34590-94-8

1 - 2.5 %

252-104-2

## 3. Hazards identification

See chapter 11 and 12

## 4. First-aid measures

General instructions

In any case show the physician the Safety Data Sheet

After inhalation

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

#### 4. First-aid measures (continued)

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.  
Summon a doctor immediately.

After ingestion

Do not induce vomiting.  
Summon a doctor immediately.

#### 5. Fire-fighting measures

Suitable extinguishing media  
compatible with all usual extinguishing media

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO<sub>2</sub>)

Nitrogen oxides (NO<sub>x</sub>)

Additional information

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

#### 6. Accidental release measures

Personal precautions

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

When picked up, treat material as prescribed under heading "Disposal".

### 7. Handling and storage

#### Handling

Instructions for safe handling  
See chapter 8 / Personal protective equipment.

Instructions for fire and explosion protection  
Not applicable.

#### Storage

Requirements for storage rooms and containers  
Keep container tightly closed and dry in a cool, well-ventilated place

Combined storage instructions  
Keep away from food, beverages and animal feedstocks.

Additional information regarding storage  
Protect from frost.  
Protect from heat and direct sunlight  
Protect from atmospheric moisture and water

### 8. Exposure controls/personal protection

Substances having workplace related exposure values/limits which may require monitoring for assessment purposes

Designation of substance		Ref./Country/Year	
CAS No.	Type		
· (2-methoxymethylethoxy)propanol			
34590-94-8	EU-TWA (8h)	308 mg/m3	2000/39/EC
34590-94-8	EU-TWA (8h)	50 ml/m3	2000/39/EC

#### Personal protective equipment

General protective and hygiene measures  
Take care for sufficient ventilation or exhaust on the workshop place.  
Avoid contact with eyes and skin  
Use barrier skin cream.  
Remove soiled or soaked clothing immediately.  
Do not eat, drink or smoke during work time.  
Wash hands before breaks and after work.

Respiratory protection  
Not applicable.

Hand protection  
Butyl rubber/nitrile rubber gloves

Eye protection  
Safety glasses

Body protection  
Working clothes

Product name: **Sikafloor Proseal W**

Date of printing: 02.11.2005

Page: 4/5

Revised: 18.04.2005

SDS No.: 014-00215065.0000

### 9. Physical and chemical properties

#### Appearance

Physical state: liquid  
Colour: white  
Odour: of ammonia

#### Data relevant to safety

#### Method

Flash point	not applicable
Density at 20°C	approx. 1.012 g/cm <sup>3</sup>
pH value at 20°C	approx. 9.5
VOC (solvents)	0.44 %
VOC (CH)	0.44 %

### 10. Stability and reactivity

#### Materials to avoid/dangerous reactions

No hazardous reactions when stored and handled according to prescribed instructions.

#### Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

### 11. Toxicological information

#### Experience on humans

When skin contact:  
May cause irritation.  
When eyes contact:  
May cause irritation.  
When inhalation:  
May cause irritation.  
When swallowed:  
May cause health disorders.

### 12. Ecological information

#### Additional information

Do not allow to enter waste water drain, waterways or soil.

### 13. Disposal considerations

#### Product

#### Recommendations

Must be disposed of in a special waste disposal unit in accordance with the corresponding regulations.  
See chapter 15, national regulations.

Product name: **Sikafloor Proseal W**

Date of printing: 02.11.2005

Page: 5/5

Revised: 18.04.2005

SDS No.: 014-00215065.0000

### 13. Disposal considerations (continued)

#### Packaging

##### Recommendations

Completely emptied packagings may be given for recycling.

Empty packaging may still contain hazardous residues.

Empty packaging should be removed by a licensed waste contractor.

### 14. Transport information

#### ADR/RID

Further information

No dangerous goods.

#### IMO/IMDG

Marine pollutant: no

Further information

No dangerous goods.

#### IATA/ICAO

Further information

No dangerous goods.

### 15. Regulatory information

Labelling according to EEC Directive

The product does not require a hazard warning label in accordance with

EC directives/the relevant national laws.

### 16. Other information

asterisk (\*) on left margin marks modification of previous version

Recommended use: Chemical product for construction and industry

R-phrases of the ingredients listed in chapter 2

38 Irritating to skin.

41 Risk of serious damage to eyes.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.